

HL-BI8027VM

8MP Starlight Bullet Network Camera



8.0MP

H.265+

WDR
(120db)

HLC

BLC

3D-DNR

IP67

ONVIF

Key Features

- Compact design, metal case
- 2.7-13.5mm motorized lens
- H.265+ encoding, 8MP@30fps
- Smart IR up to 50m
- ROI, Defog, BLC, HLC
- DC12V / PoE
- microSD up to 256 GB

SPECIFICATIONS

CAMERA

Image Sensor	1/2.8" Progressive CMOS
Effective Pixels	8MP 3840 (H) × 2160 (V)
Scanning System	PAL/NTSC
Electronic Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Support
Min. illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
S/N Ratio	44dB
IR LEDs	4pcs Array
IR Range	Up to 50m
IR On/Off Control	Auto

LENS

Starlight	Yes
Lens Type	Motorized
Iris	Fixed Iris
Focal Length	2.7 ~ 13.5 mm
F Number (Max Aperture)	F No. 1.83 (W) ~ 3.32(T)
Angle of View	Horizontal: 33 ~ 111° , Vertical: 18 ~ 57° , Diagonal: 37 ~ 134°
Focus Control	Auto
Close Focus Distance	0.8m(W) ~ 1m(T)

INTELLIGENCE

Event Trigger	Motion Event, Alarm Event, Smart Motion Detection, Face Detection, Human/Vehicle Detection, Video Tampering
IVS	Face Detection, Human/Vehicle Detection, PID, LCD, PD&VD, FD

VIDEO

Compression	H.265/H.264, H.265+/H.264+
Max. Resolution	8MP 3840(H)×2160(V)
Streaming Capability	Triple
Stream / Frame Rate	Main Stream (1~30fps) 8MP(3840x2160),5MP(2592x1944,3072x1728), 4MP(2592x1520), 3MP(2304x1296),1080P(1920x1080), 960P(1280*960),720P(1280x720), Sub Stream 720P(1280x720),VGA(640x480), QVGA(320x240) Mobile Stream VGA(640x480), QVGA (320x240)
Bit Rate	8Kbps ~ 16Mbps
Day/Night	IR cut filter with auto switch (Day/Night/Auto/Schedule)
Image Enhancement	WDR, BLC , HLC, Defog
Image Settings	Flip, Rotation, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
White Balance	Yes

Gain Control	Yes
Noise Reduction	3D DNR
El. Image Stabilization (EIS)	N/A
Digital Zoom	N/A
Smart IR	Yes
Mirror	N/A
Region of Interest	Yes
Motion Detection	Support
Privacy Masking	Support

AUDIO

Compression	G711A, G711U, G726 22K
Bit Rate	N/A

NETWORK

Ethernet	RJ45 (10/100BASE-T)
Protocols	TCP / IP, HTTP, DHCP, DNS, DDNS, RTP / RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Interoperability	ONVIF (Profile S/G/T)
Streaming Method	Unicast / Multicast
Max. User Access	Max 7 (admin+user)
Web Viewer	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower
Smart Phone	IOS, Android system

INTERFACE

Audio Interface	1 input (RCA), 1 output (RCA)
Alarm	1 input, 1 output
RS485	N/A
BNC Output	N/A
Reset Button	Yes
Edge Storage	microSD up to 256 GB
Two-way power in-out	Yes
Microphone	N/A
Speaker	N/A

ELECTRICAL

Power Supply	DC 12V/PoE
Power Consumption	≤ 7W
Operating Temperature	-30°C+55°C
Operating Humidity	less than ≤ 95% RH
Ingress Protection	IP67
Casing	Metal
Dimensions	242.12 X 87.4 X 83.88mm
Net Weight	appr. 858g

CERTIFICATIONS

Certifications	CE, RoHS, FCC
----------------	---------------

DIMENSIONS

