

HL-BQ2027M

2MP Bullet Starlight 4 in 1 Camera



2.0MP

d-WDR

3D DNR

STARLIGHT

BLC

ATW

IP67

Key Features

- 2MP, 1920x1080 resolution
- 2.7-13.5mm motorized lens
- Max IR distance 35m
- 4 in 1 (TVI, AHD, CVI, CVBS) switchable video output
- IP67

SPECIFICATIONS

CAMERA

Image Sensor	1/2.8" Sony Starvis IMX307 Starlight
Effective Pixels	1080P(1920×1080)
Scanning System	Progressive
Shutter Speed	Auto
Min. illumination	0.01lux@F1.2(AGC ON),0Lux with IR ON
S/N Ratio	40dB
IR LEDs	30x SMD LED
IR Range	35m
IR cut filter	Yes

Casing	Metal
Dimensions	240x84x77mm
Net Weight	appr. 329g

CERTIFICATIONS

Certifications	CE (EMC LVD), FCC, RoHS2.0
----------------	----------------------------

LENS

Lens Type	Motorized
Iris	Fixed
Focal Length	2.7-13.5mm
F Number (Max Aperture)	F1.8(W) ~ F3.3 (T)
Angle of View	109 - 32 °
Focus Control	Auto
Close Focus Distance	0.3m

VIDEO

Max. Resolution	1080P(1920×1080)
Frame Rate	AHD/TVI/CVI : 2MP P/@25fps N/@30fps, CVBS : 960H
Video output termination	1-channel BNC
Video interface	Switchable to AHD/TVI/CVI/CVBS
Day/Night	EXT/Auto/Color/BW
Image Enhancement	DWDR, BLC
White Balance	ATW
Gain Control	Auto
Noise Reduction	3D DNR
Electronic Image Stabilization (EIS)	No
Smart IR	No
Mirror	Reverse

AUDIO

Audio interface	No
-----------------	----

ELECTRICAL

Power Supply	DC 12V
Power Consumption	IR ON : 5W, IR OFF : 0.6W

GENERAL

Communication	up to coax, Protocol
Operating Temperature	-30°C ~ 60°C
Operating Humidity	90%
Ingress Protection	IP67

DIMENSIONS

