

HL-BQ5028V

5MP Bullet 4 in 1 Camera



5.0MP

BLC

2D DNR

d-WDR

IP67

ATW

Key Features

- 5MP, 2608x1960 resolution
- 2.8-12mm varifocal lens
- Max IR distance 35m
- 4 in 1 (TVI, AHD, CVI, CVBS) switchable video output
- IP67

SPECIFICATIONS**CAMERA**

Image Sensor	1/2.7" Progressive CMOS
Effective Pixels	5MP, 2608(H)×1960(V)
Scanning System	Progressive
Shutter Speed	Auto (PAL/NTSC)
Min. illumination	0.05lux@F1.2(AGC ON),0Lux with IR ON
S/N Ratio	39dB
IR LEDs	30pcs
IR Range	Up to 35m
IR cut filter	Yes

LENS

Lens Type	Varifocal
Iris	Fixed
Focal Length	2.8-12mm
F Number (Max Aperture)	F1.8 (W) ~ F3.2 (T)
Angle of View	H.FOV: 114 - 33 °
Focus Control	Auto
Close Focus Distance	0.3m

VIDEO

Max. Resolution	5MP (2608×1960)
Frame Rate	AHD/TVI: 5MP@20fps AHD/CVI/TVI: 4MP/P@25fps 4MP/N@30fps CVBS: 960H
Video output termination	1-channel BNC
Video interface	Switchable to AHD/TVI/CVI/CVBS
Day/Night	EXT/Auto/Color/BW
Image Enhancement	dWDR, BLC
White Balance	ATW (automatic)
Gain Control	Auto
Noise Reduction	2D DNR
Electronic Image Stabilization (EIS)	No
Smart IR	No
Mirror	Reverse

AUDIO

Audio interface	No
-----------------	----

ELECTRICAL

Power Supply	DC 12V
Power Consumption	IR ON : 4W, IR OFF : 0.6W

GENERAL

Communication	Through coax protocol
Operating Temperature	-30°C ~ 55°C
Operating Humidity	90%
Ingress Protection	IP67
Casing	Metal
Dimensions	Ø 241.18x82.18
Net Weight	Appr. 758g

CERTIFICATIONS

Certifications	CE (EMC LVD), FCC, RoHS2.0
----------------	----------------------------

DIMENSIONS